



# Forged Steel Check Valves

## Y type check valves




**CL800** Bolted bonnet, full port and reducing port  
Threaded, butt-welded or socket welded ends; design to BS 5352

Specification (NPS)	R.P	-	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3
	F.P	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2
Face to face	L	98	98	98	111	140	140	155	170	-
Height	H	70	70	70	100	110	120	120	150	-
Height (angle dimension)	d	7	10	13	17.5	23	30	35	46	-
Weight(kg)		2.2	2.2	2.1	4.2	9	8.9	10	18.6	-




**CL800** Welded bonnet, full port and reducing port  
Threaded, butt-welded or socket welded ends; design to BS5352

Specification (NPS)	R.P	-	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3
	F.P	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2
Face to face	L	79	79	92	100	140	140	155	170	-
Height	H	65	65	65	95	105	110	110	140	-
Height (angle dimension)	d	7	10	13	17.5	23	30	35	46	-
Weight(kg)		1.8	1.8	2.0	3.5	8.0	8.0	12	16	-



**CL900-CL1500** Bolted bonnet, full port  
Threaded, butt-welded or socket welded ends; design to BS 5352

Specification(NPS)	F.P	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2
Face to face	L	98	111	111	140	140	155	170	-
Height	H	70	70	100	110	110	120	150	-
Height (angle dimension)	d	9	12	15	20	28	32	40	-
Weight(kg)		2.1	4.2	9	8.9	10	18.6	20	-



**CL900-CL1500** Welded bonnet, full port  
Threaded, butt-welded or socket welded ends; design to BS5352

Specification(NPS)	F.P	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2
Face to face	L	92	100	100	140	140	155	170	-
Height	H	65	65	65	105	110	110	140	-
Height (angle dimension)	d	9	12	15	20	32	28	40	-
Weight(kg)		2.0	3.5	3.5	8.0	12	12	18	-